



An Optimal Combination of Invasive and Noninvasive Ventilator

VG70 VENTILATOR

AEOMED
Reliable Quality Thoughtful Service



Exclusive Distributor Aeonmed & Heyer For Sulawesi

PT KARYA PRATAMA

Daan Mogot Arcadia Blok F1 No. 8A-8B Jl. Daan mogot Km 21,
Kec. Batuaceper, Kel. Batuaceper, Kota Tangerang, Banten 15122
Telepon : (021) 5595 8085, Fax : (021) 5595 8125

Superior Mobile ICU Ventilator

- Comprehensive ICU ventilator including BIVENT and PRVC
- Compact, 4 hours internal batteries, turbine absed, suitable for intra-hospital transportation
- Flexible device configuration : equipped on a trolley, bed or ceiling pendant

Cost Effective Solution

- Unique metal-based, non-consumable exhalation valve
- Built-in flow sensor, non-consumable design
- Upgradeable ventilation system software, with an available USB port



360° Visible
Alarm Lamp



12" TFT Detachable
Touch Screen



Ultra Quiet
Turbine Inside



Integration Power
Supply Solution



Built-in Battery,
With Extended
Backup Option



Exclusive Distributor Aeonmed & Heyer For Sulawesi

PT KARYA PRATAMA

Daan Mogot Arcadia Blok F1 No. 8A-8B Jl. Daan mogot Km 21,
Kec. Batuaceper, Kel. Batuaceper, Kota Tangerang, Banten 15122
Telepon : (021) 5595 8085, Fax : (021) 5595 8125

KONTAK DIVISI E-CAT :

0812 9351 3876 (Kamal)
0822 1148 1678 (Endah)



An Optimal Combination of Invasive and Noninvasive Ventilator

- As noninvasive ventilation is used increasingly in a wide range of clinical situations, we offer a dual solution VG70
- Combines the advantages of a flexible noninvasive ventilator with a full-featured invasive ventilator of the ICU
- Auto-detect and adjustable leakage compensation
- Multi-parameter monitoring

Safe Ventilation Through Whole Treatment Phase



Initial Treatment Phase

- Both Invasive and noninvasive ventilation modes can be selected, meet the needs for more patient.
- User friendly interface, present patient's height and IBW.



Stable Condition Phase

- PRVC and BIVENT employ lung-protective strategies, delivering intelligent ventilation
- Comprehensive lung mechanics monitoring include compliance, airway resistance, PEEPi and time constant
- Three waveforms & three loops with user-friendly display provide a continuous monitoring of the patient's condition



Weaning Phase

- Various ventilation modes enhance the weaning process
- The unique trigger and leakage compensation system safeguards each and every patient breath resulting in smooth and comfortable breathing, avoiding extra workload on the patient and promoting recovery
- RSBI and WOB provide accurate reference for weaning



Rehab Phase

- Provides pressure support for the patient when spontaneous breathing is present
- Integrated nebulizer enhances clinical treatment option



Exclusive Distributor Aeonmed & Heyer For Sulawesi

PT KARYA PRATAMA

Daan Mogot Arcadia Blok F1 No. 8A-8B Jl. Daan mogot Km 21,
Kec. Batuaceper, Kel. Batuaceper, Kota Tangerang, Banten 15122
Telepon : (021) 5595 8085, Fax : (021) 5595 8125

KONTAK DIVISI E-CAT :


0812 9351 3876 (Kamal)
0822 1148 1678 (Endah)

Technical Specification

Ventilation Modes				
	VCV(A/C)	PCV(A/C)	PRVC	SIMV(VCV)+PSV
	SIMV(PCV)+PSV	SIMV(PRVC)+PSV	SPONT/CPAP+PSV	
	BIVENT+PSV	NIV/CPAP	NIV-T	NIV-S/T
Parameters				
• Tidal Volume:	20~2000 ml			
• Respiration Rate:	1~80 bpm			
• T _{insp} :	0.2~9 s			
• T _{slope} :	0~2 s			
• T _{pause} :	0~4 s			
• I:E Ratio:	1:10~4:1			
• FiO ₂ :	21%~100%			
• Trigger Sensitivity:	Pressure (-20~0 cmH ₂ O, above PEEP)			
	Flow (0.5~20 LPM)			
• PEEP:	0~35 cmH ₂ O			
• P _{support} :	0~70 cmH ₂ O			
• P _{insp} :	5~70 cmH ₂ O			
Special Procedures				
	Apnea Ventilation	Suction(smart O ₂ enrichment)	Manual Breath	
	Insp/ Exp Hold	*ETCO ₂ Measurement		
	Nebulization	Waveform Freeze		
Monitoring				
• Pressure Value:	P _{peak} , P _{plat} , P _{mean} , P _{min} , PEEP			
• Volume / Flow Value:	V _{ti} , V _{te} , MV, MV _{spont}			
• Time Value:	f _{total} , f _{spont} , I:E			
• Real Time Curves:	Pressure-Time, Flow-Time, Volume-Time waveforms			
	Pressure-Volume, Volume-Flow, Flow-Pressure loops			
• Gas Monitoring:	FiO ₂ , *ETCO ₂			
• Calculated Values:	Compliance(C)			
	Resistance(R)			
	MV _{leak}			
	RSBI			
	WOB			
	PEEP _i			
Alarm				
	Paw high / low MVe high / low Circuit disconnect			
	FiO ₂ high / low	Inspiration / Expiratory tidal volume low		
	High Respiration Rate	Apnea	AC Failure	Nebulizer On
	Low Battery	O ₂ supply down	High / Low PEEP	
	Leakage out of range	Occlusion		
Technical Data				
• Screen:	12" TFT color touch screen (detachable)			
• Supply Gas:	O ₂ , 0.28~0.6 MPa			
• Power Supply:	AC100~240 V, 50 Hz/60 Hz			
• Communication Interface:	Nurse call Port			
• Dimension (WxDxH):	322 mm x 375 mm x 366 mm (Main Unit)			
	547 mm x 675 mm x 950 mm (Cart)			
• Weight:	12.5 kg (Main Unit)			
	25 kg (Cart)			

AEOMED

Reliable Quality Thoughtful Service



Exclusive Distributor Aeonmed & Heyer For Sulawesi

PT KARYA PRATAMA

Daan Mogot Arcadia Blok F1 No. 8A-8B Jl. Daan mogot Km 21,
Kec. Batuaceper, Kel. Batuaceper, Kota Tangerang, Banten 15122
Telepon : (021) 5595 8085, Fax : (021) 5595 8125

KONTAK DIVISI E-CAT :

0812 9351 3876 (Kamal)
0822 1148 1678 (Endah)